

Safety Data Sheet

Product name : **NORSODYNE 6417**

Page : 1/9

SDS n° :cven15349

Version of : 2009-03-10

This sheet supersedes the one dated : 2008-10-10

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

PRODUCT NAME : NORSODYNE 6417

CHEMICAL NAME OR GENERIC NAME :
Unsaturated polyester resin

APPLICATIONS : Production of fibre reinforced composites.

SUPPLIER :
CRAY VALLEY LTD
LAPORTE ROAD
STALLINGBOROUGH, NORTH EAST LINCS. DN41 8DR
UNITED KINGDOM
Tel: +44 (0) 1469 572464
Fax: +44 (0) 1469 572988

CONTACT PERSON : Rrsn.SDSMANAGEMENT@crayvalley.com

INTERNET : <http://www.crayvalley.com>

URGENCE / EMERGENCY / EMERGENCIA / NOTRUFNUMMER / N° 24/24 :

Europe, America, Middle East, Africa (European language countries)	+44 (0) 1235 239 670
Middle East, Africa (Arabic speaking countries)	+44 (0) 1235 239 671
Asia, Pacific	+65 3158 1074

2. HAZARDS IDENTIFICATION

Flammable.

- Xn; Harmful by inhalation.
- Xi; Irritating to eyes and skin.
- Canc. Cat. 3; Limited evidence of a carcinogenic effect.
- N; Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

May produce an allergic reaction.

PHYSICAL RISKS.

The mixture of product vapour and air could be explosive.

Strongly exothermic polymerisation may be caused by:

Heat.

Free radical formers.

Peroxides.

Safety Data Sheet

Product name : **NORSODYNE 6417**

Page : 2/9

SDS n° :cven15349

Version of : 2009-03-10

This sheet supersedes the one dated : 2008-10-10

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS No.	Content	Symbol	R-phrases
styrene	202-851-5	100-42-5	~24 %	Xn	R-10, 20, 36/38
alkanes, C10-13, chloro	287-476-5	85535-84-8	~8.5 %	Xn ,N	R-40, 50/53
antimony trioxide	215-175-0	1309-64-4	~8 %	Xn	R-40
phthalic anhydride		85-44-9	0.05-0.2 %	Xn	R-22, 37/38, 41, 42/43
cobalt octoate		136-52-7	0.05-0.2 %	Xi	R-38, 43

SEE SECTION 16 FOR EXPLANATIONS TO R-PHRASES

4. FIRST AID MEASURES

INHALATION : Take person out of the contaminated area. Remove patient to fresh air.
Call a doctor in case of doubt or if symptoms persist.

INGESTION : DO NOT INDUCE VOMITING!
Put under medical supervision.
If swallowed, seek immediate medical advice and show container or label to the doctor.

SKIN : Remove contaminated clothing.
Wash with soap and water and rinse with water.

EYES : Promptly wash eyes with plenty of water while lifting the eye lids.
Continue to rinse for at least 15 minutes.
Contact physician if irritation persists.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : RECOMMENDED :
Powder, foam or CO₂.
Sand.
Water spray.
NOT SUITABLE :
Water jet.

SPECIAL FIRE FIGHTING PROCEDURES :
Cool the container with sprayed water to avoid polymerisation.
Eliminate all sources of combustion.
Treat as hydrocarbon fire.
Limit spreading of extinguishing fluids.

HAZARDOUS COMBUSTION PRODUCTS :
By combustion, formation of toxic products : carbon, carbon monoxide, carbon dioxide...

PROTECTIVE MEASURES IN FIRE : Wear individual breathing apparatus.

Safety Data Sheet

Product name :

NORSODYNE 6417

Page : 3/9

SDS n° :cven15349

Version of : 2009-03-10

This sheet supersedes the one dated : 2008-10-10

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION :	Avoid inhaling vapours. Wear protective equipment. Gloves - Goggles - Boots. Wear self-contained breathing apparatus.
ENVIRONMENTAL PROTECTION :	Do NOT discharge in sewers. Do not allow this chemical to enter the environment. If the product contaminates lakes, rivers or sewers, inform appropriate authorities in accordance with local regulations.
SPILL CLEANUP METHODS :	RECOVERY : Spread sand. Collect the product in a container pending future destruction. DISPOSAL : Burn in an approved installation for liquids. INCOMPATIBLE MATERIALS : Wood sawdust.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS :	Unloading recommended procedure : pumping or under nitrogen pressure. Collect vapours at source. Mechanical ventilation or local exhaust ventilation is required. Durind spraying wear suitable respiratory equipment. Do NOT smoke when using. Take precautionary measures against electrostatic discharges.
STORAGE PRECAUTIONS :	SUITABLE : Keep at temperature not exceeding 30 °C. Keep in cool, dry, ventilated storage and closed containers. Keep away from heat, sparks and open flame. No smoking. Equipment earthing.
STORAGE CRITERIA :	INCOMPATIBLE MATERIALS : Strong oxidizing agents. Catalysts and accelerators. PACKAGING MATERIALS RECOMMENDED : Metal packaging. GRP Tanks (Reinforced Glass Polyester). Except those not recommended. PACKAGING MATERIALS NOT SUITABLE : Aluminium. Copper or copper alloy and plastics.

Safety Data Sheet

Product name : **NORSODYNE 6417**

Page : 4/9

SDS n° :cven15349

Version of : 2009-03-10

This sheet supersedes the one dated : 2008-10-10

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient name	CAS no.	Reference	Date	LT Exp 8 Hrs	ST Exp 15 Min
styrene	100-42-5	EH 40 (HSE)	2005	100 ppm	250 ppm
antimony trioxide	1309-64-4	EH 40 (HSE)	2005	0.5 mg/m3	
phthalic anhydride	85-44-9	EH 40 (HSE)	2005	4 mg/m3	12 mg/m3

PROTECTIVE EQUIPMENT :



RESPIRATORS :

Do NOT breathe vapours.
Wear suitable respiratory protection. (AB)

PROTECTIVE GLOVES :

Wear solvent-proof gloves. (Neoprene).

EYE PROTECTION :

Wear approved safety goggles.

OTHER PROTECTION :

Wear suitable protective clothing.

HYGIENIC WORK PRACTICES :

Change work clothing daily before leaving work place.
Eating, smoking and water fountains prohibited in immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE :

Liquid.

COLOUR :

Off-white.

ODOUR :

Styrene.

PHYSICAL DATA COMMENTS :

(#) Values related to styrene, not to the preparation.
Take precautionary measures against electrostatic discharges.

BOILING POINT (°C, INTERVAL) :

> 145°C

DENSITY/SPECIFIC GRAVITY (g/ml) :

1.1 - 1.15
Temperature (°C) :20°C

VAPOUR PRESSURE :

6 hPa
Temperature (°C) :20°C

Safety Data Sheet

Product name : **NORSODYNE 6417** Page : 5/9

SDS n° :cven15349

Version of : 2009-03-10
This sheet supersedes the one dated : 2008-10-10

VISCOSITY (INTERVAL) : 3.5 - 4.5 dPas
Temperature (°C) :25°C

SOLUBILITY DESCRIPTION : Insoluble in water.
Soluble in most organic solvents.

FLASH POINT (°C) : 31°C
Method :DIN EN 22719 - ISO 2719

AUTO IGNITION TEMP. (°C) : 490°C #

FLAMMABILITY LIMIT - LOWER(%) : 1.1 #

FLAMMABILITY LIMIT - UPPER(%) : 6.1 #

10. STABILITY AND REACTIVITY

STABILITY : Stable under normal storage condition.

CONDITIONS TO AVOID : Avoid heat.
Light.
Away from sources of ignition.

POLYMERISATION DESCRIPTION : Exothermic polymerisation may occur by :
Strong oxidizing agents.
Peroxides.
Radical formers.

HAZARDOUS DECOMP. PRODUCTS :
By thermal decomposition, formation of :
Carbon.
Carbon monoxide (CO).
Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

SENSITIZATION : May produce an allergic reaction.

CARCINOGENICITY : Carcinogen Category 3.

HEALTH HAZARDS, GENERAL : Limited evidence of a carcinogenic effect.

INHALATION : Harmful by inhalation.
Symptoms and signs include : headache, dizziness, tiring.

SKIN : Irritating to skin.

EYES : Irritating to eyes.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do not discharge into drains or the environment ; dispose to an authorised waste collection point.

DEGRADABILITY : (#) Easily biodegradable.
(#) Values related to styrene, not to the preparation.

Safety Data Sheet

Product name : NORSODYNE 6417 Page : 6/9

SDS n° :cven15349

Version of : 2009-03-10
This sheet supersedes the one dated : 2008-10-10

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS : Incineration in approved installation.
Incineration for liquid resins. Crushing then incineration for solid resins.
Cleaned packaging may be recycled.
This material and its container must be disposed of as hazardous waste.

14. TRANSPORT INFORMATION

GENERAL : The data included in this section don't take into account the exemptions regarding each transport regulation.

LABEL FOR CONVEYANCE :



- ROAD TRANSPORT:

UN NO. ROAD : 1866

ADR CLASS NO. : 3

CLASSIFICATION CODE : F1

ADR PACKING GROUP : III

HAZARD NO. (ADR) : 30 Flammable liquid (flash point between 23°C and 61°C, inclusive) or flammable liquid or solid in the molten state with a flash point above 61°C, heated to a temperature equal to or above its flash point, or self heating liquid.

ADR LABEL NO. : 3

PROPER SHIPPING NAME (NATIONAL) :
RESIN SOLUTION

- RAIL TRANSPORT:

RID CLASS NO. : 3

RID ITEM NO. : III

RID PACKING GROUP : III

- SEA TRANSPORT:

UN NO. SEA : 1866

IMDG CLASS : 3

Safety Data Sheet

Product name : NORSODYNE 6417 Page : 7/9

SDS n° :cven15349

Version of : 2009-03-10
This sheet supersedes the one dated : 2008-10-10

IMDG PACKING GROUP : III
EMS NO. : F-E, S-E
MARINE POLLUTANT : No.
- AIR TRANSPORT:
UN NO., AIR : 1866
IATA/ICAO CLASS : 3
IATA/ICAO PACKING GROUP : III

15. REGULATORY INFORMATION

SYMBOLS :



CONTAINS : alkanes, C10-13, chloro

antimony trioxide

styrene

RISK PHRASES : R-10 Flammable.
R-20 Harmful by inhalation.
R-36/38 Irritating to eyes and skin.
R-40 Limited evidence of a carcinogenic effect.
R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES : Contains cobalt octoate and phthalic anhydride. May produce an allergic reaction.
S-23 Do not breathe gas/vapour.
S-36/37 Wear suitable protective clothing and gloves.
S-46 If swallowed seek medical advice immediately and show this container or label.
S-51 Use only in well-ventilated areas.
S-60 This material and its container must be disposed of as hazardous waste.
S-61 Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

Safety Data Sheet

Product name : **NORSODYNE 6417** Page : 8/9

SDS n° :cven15349

Version of : 2009-03-10
This sheet supersedes the one dated : 2008-10-10

EU DIRECTIVES : Regulation (EC) N° 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) N° 793/93 and Commission Regulation (EC) N° 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. Directive 91/155/EEC amended by Directive 93/112/EEC and Directive 2001/58/EC : Safety data sheets. Dangerous preparations : Directive 1999/45/EC amended by Directive 2001/60/EC - OJEC L226 - 22/08/2001 and Directive 2006/08/EC OJEC - 24/01/2006. Commission Directive 2004/73/EC of 29 April 2004 adapting to technical progress for the 29th time Council Directive 67/548/EEC on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances (Official Journal L 216 - 16/06/2004).

16. OTHER INFORMATION

EXPLANATIONS TO R-PHRASES IN SECTION 2 :

R-10 Flammable.
R-20 Harmful by inhalation.
R-36/38 Irritating to eyes and skin.
R-40 Limited evidence of a carcinogenic effect.
R-50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R-22 Harmful if swallowed.
R-37/38 Irritating to respiratory system and skin.
R-41 Risk of serious damage to eye.
R-42/43 May cause sensitization by inhalation and skin contact.
R-38 Irritating to skin.
R-43 May cause sensitization by skin contact.

USER NOTES:

This information ONLY applies to this product which conforms to the specification of CRAY VALLEY. In case of formulations or mixtures, the user must ensure that new hazards are not apparent in line with the above. The information contained herein is based on our knowledge of the product, at the date of publishing and it is given in good faith. Please note the possible risks involved if this product is used for applications other than those for which it is intended. This sheet shall only be used and reproduced for Health & Safety purposes. The references to legislative & regulatory information and codes of practice are not exhaustive. Other applicable regulations may be considered. It is the responsibility of the user to refer to existing legislation concerning the use, the storage and the safe handling of the product. It is also the responsibility of the user to communicate ALL information related to the protection of Health, Safety & the Environment contained within this Material Safety Data Sheet to those persons involved in the handling of this product.

REVISION DATE : 2009-03-10

REVISION NO. : 2.0

Safety Data Sheet

Product name : **NORSODYNE 6417** Page : 9/9

SDS n° :cven15349

Version of : 2009-03-10
This sheet supersedes the one dated : 2008-10-10

REV. NO./REPL. SDS GENERATED : 2008-10-10